

Product Specification of:

H₂S - Industrial Sensor / Type I-43



:: KEY FEATURE ::

Amperometric gas sensor designed for biogas applications with high H₂S concentrations in continuous mode. Sensor comes without any electronics, has a low drift and short recovery times even when highly overloaded.

All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa.

Operating Principle:	3-electrode potentiostatic cell without potentiostat
Electrical Connector:	3-pin Molex®
Sensor Lifetime:	~ 2 years
Gas Connector:	M16 x 1 thread
Measurement Range:	0 to 10,000 ppm
Maximum Overload:	up to 50,000 ppm for a short period
Sensitivity:	0.2 to 2 nA/ppm
Response Time t₉₀:	< 90 s
Warm-up Time:	8 h, when connected to bias
Bias Voltage:	+ 200 mV
Drift:	< 10 % signal/year
Zero Offset Current:	< ± 500 nA
Operating Temperature:	0 to 50 °C (increased responsetime below 0 °C)
Pressure Range:	750 to 1250 hPa
Humidity Range:	30 to 98 % RH
Interferences:	SO ₂ : < 0.3 nA/ppm CO: none NO ₂ : none NO: none
Weight:	approximately 13 g
Material in Contact with Media:	PP, PPS, PTFE, stainless steel



:: STORAGE CONDITIONS ::

Temperature Range:	recommended: 5 to 30 °C maximum: -20 to 50 °C
Ambient Pressure:	600 to 1250 hPa
Humidity:	10 to 98% RH
Shelf Life:	< 3 months recommended

:: RELATED PRODUCTS ::

Product	Part-No.	Housing Colour
H ₂ S - Sensor I-43	48 00 29	grey

This data sheet is subject to change without prior notice. [I-43-Rev_022012.doc]

page 1 of 1