

Planar Combination Antenna Y60XYD

Double WLAN 5300 MHz

Desk Mount



- **No changes and modifications on the body**
- **Mounting by adhesive bonding possible on non-metallic surfaces (adhesive bonding antenna)**
- **Our products are RoHS- and REACH-conform**



Technical Data

WLAN


| | |
|-----------------|--|
| Frequency Range | 5300 MHz |
| VSWR* | < 2.0 typ. |
| Peak Gain* | +1 dBi typ. (WLAN 3) +1 dBi typ. (WLAN 2) |

Power max. 10 W



* Measured with 0.6m cable on 30x30cm ground plane

Mechanical Data

| | |
|-----------------------|--|
| Dimensions (ØxH) | ca. 68 mm x 12 mm |
| Temperature Range | -40°C to +85°C (operating temperature) |
| Connection (Standard) | ca. 3m connecting cable RG174 low loss with WLAN/SMA(m) Other cablelengths and connectors see ordering example and connector list in Internet |



Radiation diagram (typ.)*



* Measured with 0.6m cable on 30x30cm ground plane


Mounting Instructions

- To avoid mechanical stress the antenna should not be attached on doors or flaps.
- No extra ground planes are necessary for this antenna (ground plane inside).
- Mountable on all clean, smooth and stainless surfaces.
- Don't stick the antenna under +10°C to get an optimal adhesion of the sticker.
- Clean seating nonfat before sticking by using the delivered cleaning cloth.
- First remove protection foil on one side of the sticker and stick it on the seating, avoid formation of bubbles.
- Now the other protection foil has to be removed from the sticker. Stick the antenna on with it's level side and advantage direction (cable pointing below) and apply sufficient pressure.

Delivery includes: Sticker; cleaning cloth with isopropanol

Important: Before sticking please test the adhesive bonding possibility of the material!

Ordering example



Warranty

The lawful warranty conditions apply.