



DROP-IN *American-made* DMC REPLACEMENT.



Introducing **TargetPoint DMC 600**, the first US-made, American-supported, STORM-qualified digital magnetic compass — an ideal replacement for existing DMCs.

PNI's TargetPoint DMC 600 delivers unbeatable accuracy and reliability in the harshest conditions. It is a key enabler in situational awareness, threat detection and neutralization. TargetPoint combines PNI's patented magneto-inductive sensors and measurement circuitry with a 3-axis MEMS accelerometer for unparalleled cost effectiveness and performance.

Qualified as a drop-in replacement in the STORM program, TargetPoint is an ideal choice for far target locators and laser range finders that require real-world reliability and performance.



Same specs. Made and supported in the USA.

TargetPoint provides the same performance as non-US DMCs, and is a drop-in replacement in the STORM-mLRF. The TargetPoint DMC module is extensively tested to military standards, including weapon-shock, to ensure specifications are consistently met.

From an established US small business with a proven record.

PNI Sensor has been a reliable supplier of compass modules to the military market for over 20 years.

Performance Specifications¹

| | |
|--|-----------------------|
| Azimuth (Heading) Accuracy | $\pm 0.5^\circ$ rms |
| Elevation (Pitch) & Bank (Roll) Accuracy | $\pm 0.2^\circ$ rms |
| Angular Resolution | 0.01° |
| Magnetic Field Calibrated Range | $\pm 150 \mu\text{T}$ |

I/O Characteristics

| | |
|------------------------|--|
| Data Interface | RS 232 subset (CMOS-level) |
| Communication Protocol | ASCII |
| Reporting Rate | Continuous Measurement Single Measurement |
| | 1, 2, 5, 10, and 20 Hz 10 Hz maximum |

Power Requirements

| | |
|------------------------------|------------------|
| Supply Voltage | 4.75 to 5.25 VDC |
| Average Current Draw @ 10 Hz | 225 mW max. |

Environmental Testing

| | |
|---------------------------------------|---|
| Operating Temperature | -40° C to +70° C per MIL-STD-810G, Method 501.5 and 502.5 |
| Storage (non-operational) Temperature | -57° C to +85° C per MIL-STD-810G, Methods 501.5 and 502.5 |
| Temp. Shock (non-operational) | -57° C to +71° C. 15° C/minute. Stabilized for 75 minutes at extremes. 3 cycles. |
| Shock (non-operational) | 5000 shots while mounted in STORM rangefinder system on M4 rifle |
| Vibration (non-operational) | MIL-STD-810G, Method 514.5, Procedure I — General Vibration. Random vibration per Annex C — Figure 514.5C-17, with duration of ≥ 1 hour on each of 3 axes. |

Mechanical Characteristics

| | |
|------------------------|---|
| Dimensions (L x W x H) | 1.30" x 1.22" x 0.53" (33 x 31 x 13.5 mm) |
| Max Weight | 20 gm |
| Mounting Options | Level or 90° side-mounted |

1. Specifications are preliminary and subject to change.

TARGETPOINT

DIGITAL MAGNETIC COMPASS



3-AXIS



HARD & SOFT-IRON
CORRECTION



LOW POWER



HIGH RESOLUTION/
ACCURACY



WEAPON-SHOCK
TESTED



MODULE

PNI SENSOR

is an established, successful leader in magnetometer technology, serving such clients as the US military and GM, Chrysler and Ford in the automotive industry. PNI's team of physicists, engineers and researchers has unparalleled expertise in creating the highest performance magnetic sensor on the market. PNI applies this patented magnetometer technology to create highly accurate, reliable and low power compass modules.

Many of today's leading companies are using PNI technology in their marquee products and across a wide spectrum of applications, including robotics, targeting, surveying, and oceanography.

For ordering information and most current specifications, please visit www.pnicorp.com

PNI Sensor

2331 Circadian Way, Santa Rosa, CA 95407 USA Phone: 707-566-2260 Fax: 707-566-2261

