BMYD Series



Marathon Yagi Antennas, 400 MHz Series



PCTEL's Bluewave Marathon 400 MHz frequency series is engineered to meet the requirements of a high gain, broadband, premium quality antenna. The Bluewave yagi series is manufactured using high strength 6061-T6 aluminum to withstand heavy ice, high wind and other harsh conditions. All elements are welded to the boom and the dipole design has an integral feed line welded to the boom for extra strength and electrical conductivity. This eliminates misalignment or fastener problems. The entire antenna is anodized for aesthetic appearance and corrosion resistance. A heavy-duty clamp is supplied which easily permits horizontal or vertical polarization.



BMYD403G





BWC1001A mount

Features

- Elements and boom are manufactured from aircraft quality 6061-T6 aluminum for optimum strength
- Antenna is anodized aesthetic appearance and for corrosion resistance
- · Antenna is supplied with a 2' pigtail (RG213) and N Female connector
- · Wind survival rating >150 mph

STANDARD CONFIGURATION

| Model | Cable | Connector | Elements | Mount |
|----------|------------|-----------|----------|--|
| BMYD403G | 2 ft RG213 | N Female | 3 | BWC1001 Clamp bracket for 1/2"-7/8" diameter yagis. |
| BMYD403K | 2 ft RG213 | N Female | 7 | Mounts to masts 1.25"-2.4" OD (included with all models) |
| BMYD403M | 2 ft RG213 | N Female | 11 | Mounts to masts 1.25 -2.4 OD (included with all models) |
| BMYD450G | 2 ft RG213 | N Female | 3 | BWC1001A clamp bracket for 3/4"-1" diameter yagis. |
| BMYD450K | 2 ft RG213 | N Female | 7 | Mounts to masts 1.25"-2.4" OD included |

ELECTRICAL SPECIFICATIONS - RF ANTENNA

| Model | Frequency Range | Gain | Azimuth Half Power Beamwidth | Elevation Half Power Beamwidth | Front to Back Ratio | Maximum Power | Nominal Impedance |
|----------|--------------------|---------|---------------------------------|-----------------------------------|------------------------|------------------|----------------------|
| BMYD403G | 403-430 MHz | 6.5 dBd | 104° | 62° | 15 dB | 250 watts | 50 ohms |
| BMYD403K | 403-430 MHz | 10 dBd | 52° | 46° | 20 dB | 250 watts | 50 ohms |
| BMYD403M | 403-430 MHz | 12 dBd | 44° | 39° | 20 dB | 250 watts | 50 ohms |
| BMYD450G | 450-470 MHz | 6.5 dBd | 104° | 65° | 15 dB | 250 watts | 50 ohms |
| BMYD450K | 450-470 MHz | 10 dBd | 50° | 45° | 20 dB | 250 watts | 50 ohms |

MECHANICAL & ENVIRONMENTAL SPECIFICATIONS

| Model | Dimensions* | Weight | Cross Sectional Area | _ | Lateral Thrust @ 100 mph with ½" of Ice | Bending Moment @ 100 mph |
|----------|--------------------|------------------|-------------------------|-----------|--|-----------------------------|
| BMYD403G | 18" x 13.9" x 3.2" | 2 lbs (0.9 kg) | 0.19 sq ft | 6.23 lbs | 19.44 lbs | 4.19 lb-ft |
| BMYD403K | 44" x 14.4" x 3.2" | 4 lbs (1.8 kg) | 0.48 sq ft | 18.41 lbs | 53.62 lbs | 29.4 lb-ft |
| BMYD403M | 72" x 14.4" x 3.2" | 3.5 lbs (1.6 kg) | 0.84 sq ft | 32.3 lbs | 86.5 lbs | 87.7 lb-ft |
| BMYD450G | 18" x 12.9" x 3.2" | 2 lbs (0.9 kg) | 0.18 sq ft | 5.85 lbs | 18.23 lbs | 3.87 lb-ft |
| BMYD450K | 42" x 11.8" x 3.2" | 3 lbs (1.4 kg) | 0.46 sq ft | 16.72 lbs | 48.49 lbs | 25.4 lb-ft |

^{*} Dimension do not include antenna cable.