



VCS-03 VCS Series • Top or Bottom • Level Sensor

Features

- ◆ Overall length less than 60mm
- ◆ Internal Fit
- ◆ 22mm diameter float
- ◆ Polypropylene Material

Comments

- ◆ High or Low level sensing
- ◆ N/O or N/C by float reversal
- * Reed Switch Reliability (UL File E153493)
- ◆ Encapsulated Magnet
- ◆ Interface Option Available

Applications

- ◆ Water high or low Level
- ◆ Condensate level alarm
- ◆ Chemical high or low level
- ◆ Cooling systems
- ◆ Coolant level indication

Material		Cable		
Housing Material Float Material	Polypropylene Polypropylene	Cable Length Connection Type	2 x 0.1M Stripped Cables	
Contact Material	Ruthenium	Cable Type	22 AWG 16/0.2mm PVC insulated	
loat SG Derating Temperature °C ledium lousing Colour loat Colour	0.54 -30 to 70 Water Black White	Cable Colour	Black/Black	
Mechanical Specifications		Mounting		
Shock	3 half-sine pulses of 11mS, 30G	Thread	1/8	
Vibration Float Diameter IP	35g up to 500Hz 22.3mm IP65	Fitment Mounting	Internal Fit Top or Bottom entry	

Switching


Switch Action (Reed S	witch)	SPST
Max Switching Voltage	VDC	200
Max Switching Voltage	VAC	250
Max Switching Current	t Amps	1
Max Switching Load W	att att	30

Operate Mode N/C with float at bottom

Contact Form A

Technical Drawing

VCS-03



NORTH AMERICA

Measurement Specialties, Inc., a TE Connectivity Company Phone +1-800-522-6752 Email: customercare.hmpt@te.com

EUROPE

MEAS Deutschland GmbH(Europe) a TE Connectivity Company Phone: +49-800-440-5100 Email: customercare.tlse@te.com

ASIA

Measurement Specialties (China), Ltd., a TE Connectivity Company Phone: +86-0400-820-6015 Email: customercare.shzn@te.com

TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.