



VCS-08 VCS Series • Top or Bottom • Level Sensor

Features

- ◆ Overall length less than 60mm
- ◆ Internal Fit
- ◆ 22mm diameter float
- ◆ PPS/Kynar material

Comments

- ◆ High or Low level sensing
- ◆ N/O or N/C by float reversal
- * Reed Switch Reliability (UL File E153493)
- ◆ Encapsulated Magnet
- ◆ Interface Option Available

Applications

- ◆ Deionized Water Level
- ◆ Alcohols
- ◆ Drinking water level
- ◆ Boiler heating element protection
- ◆ Boiling Water

Material		Cable	
Housing Material Float Material	Kynar PPS	Cable Length Connection Type	2 x 0.1M Stripped Cables
Contact Material	Ruthenium	Cable Type	22 AWG 16/0.2mm PVC insulated
Float SG Operating Temperature °C Medium Housing Colour Float Colour	0.85 -30 to 110 Hot Water Neutral Black	Cable Colour	Black/Black
Mechanical Specifications		Mounting	
Shock	3 half-sine pulses of 11mS, 30G	Thread	M8 x 1.25mm
Vibration Maximum Pressure Float Diameter IP	35g up to 500Hz 1.3 Bar 22.3mm IP65	Fitment Mounting	Internal Fit Top or Bottom entry
Switching		Technical Drawing	
Switch Action (Reed Switch) Max Switching Voltage VDC Max Switching Voltage VAC Max Switching Current Amps Max Switching Load Watt	SPST 200 250 1 30	VCS-08	
Operate Mode	N/C with float at bottom stop		M8 x 1.25 Pitch
Contact Form	A	- A	
		12 (0.47) Hex 15 Nom (0.59) Float Travel	Fixing nut O-ring

NORTH AMERICA

Measurement Specialties, Inc., a TE Connectivity Company Phone +1-800-522-6752 Email: customercare.hmpt@te.com

EUROPE

MEAS Deutschland GmbH(Europe) a TE Connectivity Company Phone: +49-800-440-5100 Email: customercare.tlse@te.com

(2.32)

45

(1.77)

22 Max

(0.87)

ASIA

22.30 Max (0.87)

> Measurement Specialties (China), Ltd., a TE Connectivity Company Phone: +86-0400-820-6015 Email: customercare.shzn@te.com

-Float Stop

TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.