



# **PS1021**

# PS1 Series Position Sensor

## **Features**

- ◆ Adjustable with XY axis using appropriate magnets
- ◆ Cable wiring from the Left of the package
- Repeatability of operation
- Shunt or direct magnet operation
- Multiple Mode of Operation

## Comments

- Robust Nylon Housing
- Normally Closed
- Surface Mounted by fixing screws
- Fully encapsulated
- ◆ Matching Magnet PM101 or PM102

# **Applications**

- ◆ Door Interlocks
- Hook Switches
- Security Systems
- Safety Interlocks
- Position Indication

POSITION SENSOR /// PS 1021 06/2017 Page 1

#### Material

Housing Material Glass Filled Nylon 6.6

Contact Material Ruthenium
Operating Temperature °C -30 to 105
Housing Colour Black

# **Mechanical Specifications**

Shock50g for 11ms durationVibration35g up to 500Hz

IP IP65

## Switching

Switch Action (Reed Switch) SPST
Max Switching Voltage VDC 175
Max Switching Voltage VAC 125

Max Switching Current Amps 0.4 (DC) 0.28 (AC)

Max Switching Load Watt 5

Operate Mode Direct Axis, Parallel Axis

Contact Form B

#### Cable

Cable Length 2 x 0.5M

Connection Type Stripped Cables


Cable Type 24AWG, 7/0.2mm PVC insulated

Cable Colour Black/Blue

## Mounting

Fitment Surface
Mounting Any Axis

# **Technical Drawing**



#### **NORTH AMERICA**

Measurement Specialties, Inc., a TE Connectivity Company Phone +1-800-522-6752 Email: customercare.hmpt@te.com MEAS Deutschland GmbH(Europe)

**EUROPE** 

a TE Connectivity Company Phone: +49-800-440-5100 Email: customercare.tlse@te.com

## ASIA

Measurement Specialties (China), Ltd., a TE Connectivity Company Phone: +86-0400-820-6015 Email: <a href="mailto:customercare.shzn@te.com">customercare.shzn@te.com</a>

#### TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.